



TYPICAL INSTALLATION - MOUNTS ON SIDE OF CONTROLLER

DUAL METER SERVICE PEDESTAL

TYPICAL APPLICATIONS INCLUDE
HIGHWAY, STREET AND
SIGN LIGHTING AND
TRAFFIC SIGNAL CIRCUITS

CITY OF CORONA STANDARD NO. 510

STANDARD FEATURES

- (2) METER SOCKET WITH TEST BLOCKS 4 JAW
- UTILITY LANDING LUGS 250 KCML
- STANDARD VOLTAGE 120/240VAC 1 PHASE 3 WIRE
- CIRCUIT BREAKER INTERIOR COPPER BUS
- (2) 8 CIRCUIT 125 AMP
- PHOTOELECTRIC SOCKET
- EXPOSED WATT HOUR METERS

SPECIFICATIONS

- * ALL COMPONENTS UL LISTED
- * NEMA 3R CONSTRUCTION
- * POLYESTER POWDER-COATED FINISH
EXCEEDS ASTM B-117 SPECIFICATIONS
- * FABRICATED FROM CORROSION-RESISTANT
ZINC COATED STEEL
- * LIGHT GREEN COLOR NO. 14672 PER
FEDERAL SPECIFICATIONS 595 -
CUSTOM COLORS AVAILABLE
- * ALL FACTORY WIRING 600 VOLT RATED COPPER
- * ALL EXTERIOR DOORS AND COVERS PADLOCKABLE
- * UTILITY COVERS SEALABLE