



OPTIONAL FEATURES

STAINLESS STEEL ENCLOSURE
 VOLTAGES AVAILABLE UP TO 480VAC 3-PHASE
 SHORT CIRCUIT RATING UP TO 42,000 AIC
 UL LISTED SERIES CONNECTED AND
 FULL RATED AIC CIRCUIT BREAKERS
 CLASS T FUSED PULLOUT DISCONNECT AVAILABLE
 CIRCUIT BREAKER INTERIORS AND PANELBOARDS
 WITH COPPER OR ALUMINUM BUS
 PHOTOELECTRIC SOCKETS

TEST SWITCHES AND SELECTOR SWITCHES
 TIMECLOCKS
 TRANSFORMERS
 CONTACTORS, ELECTRICALLY AND MECHANICALLY HELD
 MERCURY RELAYS
 MOTOR STARTERS
 THERMOSTATS, FANS AND HEATERS
 DUPLEX AND TWISTLOCK RECEPTACLES
 PIN AND SLEEVE RECEPTACLE, 200 AMPS MAXIMUM
 EMERGENCY POWER TRANSFER SWITCHES

OTHER EQUIPMENT AND FEATURES AVAILABLE -
 CONSULT YOUR FACTORY REPRESENTATIVE

SPECIFICATIONS

- * COMPLIES WITH EUSERC STANDARDS & DWG. 309
- * 12 GA. NEMA 3R CONSTRUCTION
- * POLYESTER POWDER-COATED FINISH
 EXCEEDS ASTM B-117 SPECIFICATIONS
- * FABRICATED FROM CORROSION-RESISTANT
 ZINC COATED STEEL

- * LIGHT GREEN COLOR NO. 14672 PER
 FEDERAL SPECIFICATIONS 595 -
 CUSTOM COLORS AVAILABLE
- * ALL FACTORY WIRING 600 VOLT RATED COPPER
- * ALL COMPONENTS UL LISTED
- * ALL EXTERIOR DOORS AND COVERS PADLOCKABLE
- * UTILITY COVERS SEALABLE